HD FLEET SAE 70 API CH-4 ACEA E5



Description

BENZOL® HD Fleet SAE 70 API CH-4 is monograde mineral motor oil, recommended for the lubrication of all types of heavy-duty diesel engines with or without turbocharging, heavy duty vehicle engines, engines in agricultural, construction and mining industry.

Applications

BENZOL® HD Fleet SAE 70 can be used in older trucks and buses as well as for cost effective lubrication in off-highway applications such as agricultural tractors.

Specifications and Approvals

API CH-4, ACEA E5, MB-Approval 228.0, MAN 270, MIL-L 2104 E, MTU Oil Type 1.

Performance Benefits

- High thermal and oxidation stability.
- Fuel economy and better cold starting.
- Good detergent and dispersant qualities.
- Excellent engine cleanliness and wear protection.
- Maintains engine power and efficiency and lowers servicing costs.

Product/Part Number

HD23402331	4 x 5	HD23402321	4 x 4
HD23402171	12 x 1	HD23402171	24 X 1
HD23402511	1 x 20	HD23402531	1 x 25
HD23402561	1 x 200	HD23402571	1 x 208
HD23402601	1x1000		

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L3.0
Density @ 15 °C, kg/L	D-1298	0.8865
Viscosity @ 100 °C, cSt	D-445	26.10
Viscosity @ 40 °C, cSt	D-445	279.5
Viscosity index	D-2270	122
Flash Point, °C (COC)	D-92	246
Pour Point, °C	D-97	-18
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	10.1

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

© Copyright 2021 Benzol Lubricants | All Rights Reserved.

CUSTOMER CARE
info@benzollubricants.de
www.benzollubricants.de