2T SUPER MARINE SAE 30 API TC-W



Description

BENZOL® 2T Super Marine Outboard Oil SAE 30 API TC-W is a premium quality Two cycle, Water Cooled, type 2 formula low ash two-stroke lubricant designed to meet the most critical requirement of all air cooled and water-cooled outboard engines.

Applications

BENZOL® 2T Super Marine Outboard Oil is designed for water-cooled two-stroke engines used in outboard marine applications. Mixing with the fuel should be in accordance with the manufacturer's recommendations.

Specifications and Approvals

API TC, NMMA TC-W

Technical Specifications

Performance Benefits

- Complete and quick miscibility with petrol.
- Exceptional lubricating capacity, preventing piston seizure.
- High anti-wear capacity.
- Reduced Maintenance Costs.
- Approved for use with most ethanol blended fuels
- Outstanding results in reducing visible smoke and particle emissions.

Product/Part Number

OF18010331	4 x 5	OF18010321	4 x 4
OF18010171	12 x 1	OF18010171	24 X 1
OF18010511	1 x 20	OF18010531	1 x 25
OF18010561	1 x 200	OF18010571	1 x 208
OF18010601	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	Green/Blue
Density @ 15 °C, kg/L	D-1298	0.8725
Viscosity @ 100 °C, cSt	D-445	11.15
Viscosity @ 40 °C, cSt	D-445	75.60
Viscosity index	D-2270	138
Flash Point, °C (COC)	D-92	196
Pour Point, °C	D-97	-33
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	5.2
Sulphated Ash, %	D-874	<0.05

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

© Copyright 2021 Benzol Lubricants | All Rights Reserved.

CUSTOMER CARE
info@benzollubricants.de
www.benzollubricants.de