Product Data Sheet

2T RACER LITE SAE 30 API TC JASO FD

Description

BENZOL® 2T Racer Lite SAE 30 API TC is premium quality 2 stroke oil. It is suitable for the use with unleaded gasoline also. It is formulated with high quality mineral base oil with advance performance additive technology and special solvents that permits ready mixing with gasoline over a wide temperature range



Applications

BENZOL® 2T Racer Lite has been developed for two-stroke engines operating under a range of varied conditions. It is recommended for use in the applications for air-cooled 2-stroke engines light motorbikes and scooters.

Performance Benefits

- Avoid sparks plug fouling.
- Burns without leaving any sticky deposits.
- Improved cold starting for daily use.
- Helps prevent spark plug whiskering and corrosion.
- Good lubricity through specially selected mineral base stocks.

Specifications and Approvals

API TC, JASO FD, ISO-L-EGD.

Product/Part Number

2T19100331	4 x 5	2T19100321	4 x 4
2T19100171	12 x 1	2T19100171	24 X 1
2T19100511	1 x 20	2T19100531	1 x 25
2T19100561	1 x 200	2T19100571	1 x 208
2T19100601	1x1000		

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	Green/Blue
Density @ 15 °C, kg/L	D-1298	0.8795
Viscosity @ 100 °C, cSt	D-445	11.95
Viscosity @ 40 °C, cSt	D-445	101.5
Viscosity index	D-2270	110
Flash Point, °C (COC)	D-92	200
Pour Point, °C	D-97	-15
Foam SEQ.I/II/III	D-892	0/0/0
Sulphated Ash, m%	D-874	0.09

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

© Copyright 2021 Benzol Lubricants | All Rights Reserved.

CUSTOMER CARE
info@benzollubricants.de
www.benzollubricants.de