Product Data Sheet

EFFICIENT DRIVE SAE 10W30 API SN/CF ACEA A3/B4

Description

BENZOL® Efficient Drive SAE 10W30 API SN/CF is a high range quality lubricant, synthetic, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road and highway, under extreme conditions in all seasons.



Applications

BENZOL® Synthetic SAE 10W30 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment engines. For all-season use in engines operating on gasoline, high-ethanol gasoline and without turbo-charging and direct injection.

Specifications and Approvals

API SN/CF, ACEA A3/B4, ILSAC GF-5, CHRYSLER 6395, FORD WSS-M2C9-A, MB 229.1/229.3, RN 0700/0710, GM 6094M/4718M, VW 502.00/505.00

Performance Benefits

- Enhanced fuel economy properties.
- Excellent anti-wear characteristics.
- Excellent low temperature capabilities.
- Increase engine efficiency.
- Advanced synthetic formula.

Product/Part Number

ED09624332	4 x 5	ED09624322	4 x 4
ED09624172	12 x 1	ED09624172	24 X 1
ED09624512	1 x 20	ED09624532	1 x 25
ED09624562	1 x 200	ED09624572	1 x 208
ED09624602	1x1000		

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8650
Viscosity @ 100 °C, cSt	D-445	10.75
Viscosity @ 40 °C, cSt	D-445	67.85
Viscosity index	D-2270	148
Flash Point, °C (COC)	D-92	230
Pour Point, °C	D-97	-36
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	10.2
CCS at -25°C (mPa.s)	D-5293	6050

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

© Copyright 2021 Benzol Lubricants | All Rights Reserved.

CUSTOMER CARE
info@benzollubricants.de
www.benzollubricants.de