Product Data Sheet

COMFORT DRIVE SAE 25W60 API SL/CF ACEA A3/B3

Description

BENZOL® Comfort Drive SAE 25W60 API SL/CF is formulated from quality mineral base stocks combined with multifunctional additive package. It has perfect lubricating properties and viscosity stability combined with deposit and wear control.



Applications

BENZOL® Mineral SAE 25W60 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment and 4 strokes engines under the most severe and varied operating conditions.

Specifications and Approval

API SL/CF ACEA A3/B3, VW 501.00/505.00

Performance Benefits

- Improved oxidation resistance.
- Excellent anti-wear characteristics.
- Excellent low temperature capabilities.
- Protection from piston deposits and maintains engine cleanliness.
- Increase engine efficiency.
- Provides improved fuel economy.

Product/Part Number

CD24423331	4 x 5	CD24423321	4 x 4
CD24423171	12 x 1	CD24423171	24 X 1
CD24423511	1 x 20	CD24423531	1 x 25
CD24423561	1 x 200	CD24423571	1 x 208
CD24423601	1x1000		

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, kg/L	D-1298	0.8830
Viscosity @ 100 °C, cSt	D-445	23.50
Viscosity @ 40 °C, cSt	D-445	216.2
Viscosity index	D-2270	135
Flash Point, °C (COC)	D-92	242
Pour Point, °C	D-97	-24
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	8.2

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL product, please visit www.benzollubricants.de

© Copyright 2021 Benzol Lubricants | All Rights Reserved.

CUSTOMER CARE
info@benzollubricants.de
www.benzollubricants.de